



# Dryer Group DEHUMIDIFIER

## Features :

- Auto Defrost & Water Pump Drain
- Low noise 65 dB (A) at a distance of 1 m.
- R410 Refrigerant makes the dehumidifier unit.
- Nylon filter with in dehumidifier , which is easily removed for cleaning by water or dry.
- Dehumidifier Operated between temperature 5-38 °C and working 10-95 %RH
- With continued by automatic control and digital display
- Rotary Compressor. Can set the opening and closing time
- The body casing is made of ABS Plastic
  - + Steel Dryer Powder Coated Rubust Body.



## SPECIFICATION LIST:

MODEL	DG-1300
➤ APPLIED AREA (2.6-3M HIGH)	➤ 120-140 SQ.M.
➤ POWER SOURCE/VOLTAGE	➤ 220V/ 50 Hz
➤ RATE POWER INPUT	➤ 1700W
➤ RATE POWER CURRENT INPUT	➤ 8A
➤ REFRIGERANT	➤ R410
➤ CAPACITY	➤ 130L / 24 HRS ( 30 °C/ 80%RH )
	➤ 135L / 24 HRS ( 30 °C/ 90%RH )
➤ TANK CAPACITY	➤ Direct Drain
➤ DIMENSION	➤ 1027 x 480 x 428 mm
➤ WEIGHT	➤ 60 Kg
➤ AIR FLOW	➤ 1050M3/h



**DRYER GROUP**

341/2 Moo 2 Ban Khlong Suan, Pra Samut Chedi, Samut Prakan 10290

*Tel.02-0127-477 , 02-012-7478 Fax.02-0902-398*

[www.dryergroup.co.th](http://www.dryergroup.co.th) / e-mail: [sales@dryergroup.co.th](mailto:sales@dryergroup.co.th)