



Dryer Group DEHUMIDIFIER

Features :

- Auto Defrost & Water Pump Drain
- Low noise 73 dB (A) at a distance of 1 m.
- R22/410C Refrigerant makes the dehumidifier unit.
- Nylon filter with in dehumidifier , which is easily removed for cleaning by water or dry.
- Dehumidifier Operated between temperature 3-35 °C and working 20-95 %RH
- With continued by automatic control and digital display
- Daikin Rotary Compressor.Low pressure switch
- The body casing is made of ABS Plastic
 - + Steel Dryer Powder Coated Rubust Body.



SPECIFICATION LIST:

MODEL	DG-2400
➤ APPLIED AREA (2.6-3M HIGH)	➤ 240-300 SQ.M.
➤ POWER SOURCE/VOLTAGE	➤ 380V/ 50 Hz
➤ RATE POWER INPUT	➤ 4150W
➤ RATE POWER CURRENT INPUT	➤ 7A
➤ REFRIGERANT	➤ R22/R410
➤ CAPACITY	➤ 240L / 24 HRS (30 °C/ 80%RH)
	➤ 245L / 24 HRS (30 °C/ 90%RH)
➤ AIR FLOW	➤ 2500 CMH
➤ TANK CAPACITY	➤ Direct drainage (Auto pump)option
➤ DIMENSION	➤ 761 x 573 x 1797 mm
➤ WEIGHT	➤ 168 Kg



DRYER GROUP

341/2 Moo 2 Ban Khlong Suan, Pra Samut Chedi, Samut Prakan 10290

Tel.02-0127-477 , 02-012-7478 Fax.02-0902-398

www.dryergroup.co.th / e-mail: sales@dryergroup.co.th