



DRYER GROUP บริษัท ทรายเออร์ กรุ๊ป จำกัด

## SPECIFICATION SHEET

Tel: 02-012-7477-8 Fax:02-090-2398

Web: [www.Dryer Group.co.th](http://www.Dryer Group.co.th) Email: [sales@dryergroup.co.th](mailto:sales@dryergroup.co.th)

### DG-5600



Automated cream



G4 filter



Model Number	DG-5600
Series	Industrial
Certificate	CCC
Voltage/Cycle	380V/50Hz
Power input (W)	6700
Drainage methods	Direct drainage
Dehumidifying capacity	500 L/day (30°C, 80%RH)
N/W (Kg)	195
G/W (Kg)	210
Refrigerant	R410a
Applied area (2.6-3m height)	450-700 sq.m.
Operating temperature	5°C-38°C
Control type	LED display, Micro-computer control
Sensor	Humidity sensor
Compressor	Panasonic Scroll
Safety	3 minutes delay protection
Air Flow	5600 CMH
Air inlet size	
Air outlet size	
Unit dimension (mm)	1195×500×1745

### FEATURES:

1. Huge air circulation, front air intake and side discharge.
2. Auto defrosting when ambient temp. is below 18 °C
3. Control the humidity automatically with setting humidity level. Automatically stop when humidity under control.
4. LED display, Micro-computer control.
5. Swivel casters are installed to move the machine freely.
6. CONTINUOUSLY DRAINS the dehumidifier
7. Japan SHINYEI humidity sensor, control the humidity precisely.
8. Casing steel powder color coating



High-energy rotary compressor



Compressor three minutes delay protection, high voltage protection and leakage protection

341/2 Moo 2 Ban Khlong Suan, Pra Samut Chedi, Samut Prakan 10290 341/2 หมู่ 2 ต.บ้านคลองสวน อ.พระสมุทรเจดีย์ จ.สมุทรปราการ

Tel 02-012,7477,02- 012-7478 Fax. 02-0902-398

เลขประจำตัวผู้เสียภาษี/ TAX ID.0105552033166