



DRYER GROUP บริษัท ตรายเออร์ กรุ๊ป จำกัด

SPECIFICATION SHEET

Tel: 02-012-7477-8 Fax:02-090-2398

Web: www.Dryer Group.co.th Email:sales@dryergroup.co.th

DG-830E



Model Number	DG-830E
Series	Commercial
Certificate	CE
Voltage / Cycle	220V/50Hz
Power input (W)	300W
Dehumidifying capacity	30L/day (30C , 80%RH)
Drainage method	Water tank 5.1 L or Direct drainage
N.Weight	14.5 Kg
G.Weight	15.5 Kg
Maneuverability	4 wheels
Refrigerant	R410a
Applied area (2.6-3m height)	35-40 sq.m.
Control type	88display,Electronic control
Sensor	Humidity sensor
Safety	3 minutes delay protection,Auto Defrost
Air Flow	310 CMH
Fan speed	Low - High
Clean air system	Cabon filters,Negative Ion
Working Temperature	5- 38 C
Working Humidity	20 -95%RH
Unit dimension (mm)	436×290×720

FEATURES:

1. Auto defrosting when ambient temp. is below 18 °C
2. Control the humidity automatically with setting humidity level. Automatically stop when humidity under control.
3. LED display, Micro-computer control.
4. Swivel casters are installed to move the machine freely.
5. Water tank full tip protection
6. Triple filters for clean air
7. Casing ABS Pastic
8. Time set to open or close the machine

